

ROHS Compliant



台灣駿品端子股份有限公司






TAIWAN KING PIN TERMINAL CO.,LTD

台北縣樹林市俊德街 23 號

TEL:886-2-26895596,26886112 FAX:886-2-26886110



E-mail:info@tkp.com.tw

http://www.tkp.com.tw



NOTE :

- * Material : Nylon UL 94V-0(Lead Free)
- * Color : Black
- * Current rating : 5A, AC/DC
- * Voltage rating : 250V, AC/DC
- * Mates with H6630R1 receptacle housings
- * 2-24 circuits available
- * Dual row



RECOMMENDED PCB LAYOUT

CIRCUITS	PART NO.	DIM. A	DIM. B
2	P6630I-02	---	6.70
4	P6630I-04	3.00	9.70
6	P6630I-06	6.00	12.70
8	P6630I-08	9.00	15.70
10	P6630I-10	12.00	18.70
12	P6630I-12	15.00	21.70
14	P6630I-14	18.00	24.70
16	P6630I-16	21.00	27.70
18	P6630I-18	24.00	30.70
20	P6630I-20	27.00	33.70
22	P6630I-22	30.00	36.70
24	P6630I-24	33.00	39.70

PART NO.	P6630I-XX(LF)			Part NO.	Material	Color/Finish	Remark	APPROVAL
TITLE	3.00mm Wire to Wire							DRAWN: 黃元珍
THIRD ANGLE	SCALE	UNIT	SHEET NO	TOLERANCE	DATE	ODD NUMBERS	REV	CHECKED: 王忠
	2:1	mm	1/1	.X±0.30 .XXX±0.10 .XX±0.20 ANGLE±2°	2006.07.04	ENG950001	A0	APPROVED: 馮凌杰
	300-012		C300-004					