


DIN 46237, ausgenommen*

Temperaturbeständigkeit:
-55°C bis +105°C

3595A

DIN 46237, excepté*

Résistant à une température de :
-55°C à +105°C



DIN 46237, except*

Temperature range:
-55°C up to +105°C

mm² (AWG)	für Bolzen pour borne for stud	Farben Couleurs Colours	Artikel-Nr. Numéro d'article Part-No.	DIN 46 237	øD mm	øD1 mm	øD3 mm	øD4 mm	øD5 mm	L mm	A mm	R mm	S mm	Stand.- Packg	Werkzeuge Outils Tools			
0.1-0.5 (26-22)	M2		3595A	*	2.2	1	5	2.3	-	14	4	5	0.5	500	3974N 3984L			
	M3		3596A	*	3.2	1	5	2.3	-	14	4	5	0.5	500				
	M3.5		35961A	*	3.7	1	6.5	2.3	-	16	4	5	0.5	500				
	M4		3597A	*	4.3	1	6.5	2.3	-	16	4	6	0.5	500				
	M5		3598A	*	5.3	1	8	2.3	-	16	4	6.5	0.5	500				
0.5-1 (22-18)	M2		3600A	*	2.2	1.6	6	4	-	17	5	4.5	0.8	500	3974N 3984C 3986N 3986S 3984O			
	M2.5		3602A	2.5-1	2.7	1.6	6	4	-	16	5	4.5	0.8	500				
	M3		3604A	3-1	3.2	1.6	6	4	-	17	5	4.5	0.8	500				
	M3.5		3608A	3.5-1	3.7	1.6	6	4	-	17	5	4.5	0.8	500				
	M4		3612A	*	4.3	1.6	7	4	-	17.5	5	5.5	0.8	500				
	M4		3614A	4-1	4.3	1.6	8	4	-	18	5	6	0.8	500				
	M5		3615A	*	5.3	1.6	8	4	-	18.5	5	6	0.8	500				
	M5		3615AW	*	5.3	1.6	8	4	-	17	5	6	0.8	500				
	M5		3616A	5-1	5.3	1.6	10	4	-	19	5	6.5	0.8	500				
	M6		3618A	*	6.5	1.6	10	4	-	19	5	6.5	0.8	500				
	M6		3619A	*	6.5	1.6	12	4	-	22	5	10	0.8	500				
	M8		3621A	*	8.4	1.6	14	4	-	23	5	10	0.8	500				
	1.5-2.5 (16-14)		M3		3625A	3-2.5	3.2	2.3	6	4.5	-	17	5	4.5		0.8	500	3974N 3984C 3986N 3986S 3984O
			M3.5		3627A	3.5-2.5	3.7	2.3	6	4.5	-	17	5	4.5		0.8	500	
M3.5		3629A	*		3.7	2.3	6	4.5	-	17	5	4.5	0.8	500				
M4		3633A	*		4.3	2.3	6.8	4.5	-	17.6	5	4.5	0.8	500				
M4		3633AW	*		4.3	2.3	6	-	5.1	17	5	4.5	0.8	500				
M4		3635A	4-2.5		4.3	2.3	8	4.5	-	18	5	6	0.8	500				
M5		3636A	*		5.3	2.3	8	4.5	-	19.5	5	6	0.8	500				
M5		3637A	5-2.5		5.3	2.3	10	4.5	-	20	5	6.5	0.8	500				
M6		3639A	6-2.5		6.5	2.3	11	4.5	-	22	5	7.5	0.8	500				
M6		3639AW	*		6.5	2.3	11	-	5.1	22	5	7.5	0.8	500				
M8		3645A	8-2.5		8.4	2.3	14	4.5	-	23	5	10	0.8	20				
M10		3647A	*		10.5	2.3	18	4.5	-	24.5	5	13	0.8	200				
M12		3649A	*		13	2.3	18	4.5	-	26	5	13	0.8	200				
M16		3650A	*		17	2.3	27	4.5	-	32	5	16	0.8	200				