



LiV-t

Hook-up Wire 105°C (similar to VDE 0812)

APPLICATION

Flexible Installation in electronic equipments

CONSTRUCTION

Conductor	Stranded bare copper
Stranding	see table
Insulation	PVC 105°C
Colours	DIN 47100

TECHNICAL DATA

Test voltage	acc to VDE 0812
Insulation resistance	min 200 MOhm*km
Max operating voltage	acc to VDE 0812
Temperature range static	-30°C to +105°C
Temperature range operating	-10°C to +105°C
Flame retardant	acc to DIN VDE 0482 part 332-1-2 / IEC 60332-1-2

REMARKS

Also available with VDE 0812 (70°C)

Cross Section (mm ²) / AWG	Conductor	Copper Index (kg/km)	Core Ø ca. mm	P/N
0,08	7 x 0,12	0,8	0,80	02012751
0,14	18 x 0,10	1,4	1,10	02012755
0,25	14 x 0,15	2,5	1,30	02012759
0,34	7 x 0,25	3,4	1,55	02012761
0,50	16 x 0,20	5	1,80	02012773
0,75	24 x 0,20	7,5	2,00	02012765
1,00	32 x 0,20	10	2,10	02012767
1,50	30 x 0,25	15	2,60	02012769

