



		Cikkszám	Típus	Gyártó	Tokozás		Átvitel		Sebesség [Mbit/s]	Hőtart. [°C]	Egység a buszon	Megjegyzés
					Normál	SMD	Fél dupl.	Duplex				
DIP14		38-09-39	MAX 1480 BCPI	MAX	DIP28	-	●	-	0,25	0..70	-	
		38-13-84	MAX 1480 BEPI	MAX	DIP28	-	●	-	0,25	-40..85	-	
DIP28		38-16-92	MAX 1480 CCPI	MAX	DIP28	-	●	-	0,25	0..70	-	
		38-14-99	MAX 1487 CPA	MAX	DIP8	-	●	-	2,5	0..70	128	
		38-25-35	MAX 1487 CSA/SMD	MAX	-	S08	●	-	2,5	0..70	128	
		38-25-36	MAX 1487 ECPA	MAX	DIP8	-	●	-	2,5	0..70	128	
		38-25-37	MAX 1487 ECSA/SMD	MAX	-	S08	●	-	2,5	0..70	128	
DIP8		38-21-90	MAX 1487 EESA/SMD	MAX	-	S08	●	-	2,5	-40..85	128	
		38-30-95	MAX 1487 EPA+	MAX	DIP8	-	●	-	2,5	-40..85	128	
		38-13-85	MAX 1490 ACPG	MAX	DIP24	-	-	●	2,5	0..70	-	
		38-13-86	MAX 1490 AEPG	MAX	DIP24	-	-	●	2,5	-40..85	-	
		38-11-36	MAX 1490 BCPG	MAX	DIP24	-	-	●	0,25	0..70	-	
		38-13-82	MAX 1490 BEPG	MAX	DIP24	-	-	●	0,25	-40..85	-	
		38-20-44	MAX 3080 CPD	MAX	DIP14	-	-	●	0,115	0..70	256	
		38-20-45	MAX 3080 CSD/SMD	MAX	-	S014	-	●	0,115	0..70	256	
S014		38-18-61	MAX 3081 CPA	MAX	DIP8	-	-	●	0,115	0..70	256	
		38-25-38	MAX 3082 CPA	MAX	DIP8	-	●	-	0,115	0..70	256	
		38-21-88	MAX 3082 ESA/SMD	MAX	-	S08	●	-	0,115	-40..85	256	
		76-01-12	MAX 3085 EESA	MAX	-	S08	●	-	0,5	-40..85	256	
		38-25-97	MAX 3095 CPE	MAX	DIP16	-	-	●	10	0..70	128	
S08		76-00-78	MAX 3160 CAP/SMD	MAX	-	SSOP20	●	●	-	0..70	-	RS232/485/422
		76-00-65	MAX 3442 EESA/SMD	MAX	-	S08	●	-	0,25	-40..85	128	RS485
		38-17-50	MAX 3480 ACPI	MAX	DIP28	-	●	-	2,5	0..70	-	Ucc=3,0..3,6V
		38-17-53	MAX 3480 AEPI	MAX	DIP28	-	●	-	2,5	-40..85	-	Ucc=3,0..3,6V
		38-17-51	MAX 3480 BCPI	MAX	DIP28	-	●	-	0,25	0..70	-	Ucc=3,0..3,6V
SSOP20		38-17-54	MAX 3480 BEPI	MAX	DIP28	-	●	-	0,25	-40..85	-	Ucc=3,0..3,6V
		38-11-04	MAX 3485 CPA	MAX	DIP8	-	●	-	10	0..70	32	Ucc=3,0..3,6V
		38-15-26	MAX 3485 CSA/SMD	MAX	-	S08	●	-	10	0..70	32	Ucc=3,0..3,6V
		38-27-75	MAX 3488 ESA/SMD	MAX	-	S08	-	●	0,25	-40..85	32	Ucc=3,0..3,6V
		38-13-51	MAX 481 CPA	MAX	DIP8	-	●	-	2,5	0..70	32	
		38-22-16	MAX 481 CSA/SMD	MAX	-	S08	●	-	2,5	0..70	32	
		38-18-08	MAX 483 CPA	MAX	DIP8	-	●	-	2,5	0..70	32	
		38-18-09	MAX 483 CSA/SMD	MAX	-	S08	●	-	2,5	0..70	32	
		38-22-43	MAX 483 EPA	MAX	DIP8	-	●	-	0,25	-40..85	32	
		38-10-10	MAX 485 CPA	MAX	DIP8	-	●	-	2,5	0..70	32	
		38-10-83	MAX 485 CSA/SMD	MAX	-	S08	●	-	2,5	0..70	32	
		38-22-17	MAX 485 EEPA	MAX	DIP8	-	●	-	2,5	-40..85	32	
		38-22-18	MAX 485 EESA/SMD	MAX	-	S08	●	-	2,5	-40..85	32	
		38-09-29	MAX 485 EPA	MAX	DIP8	-	●	-	2,5	-40..85	32	
		38-09-58	MAX 485 ESA/SMD	MAX	-	S08	●	-	2,5	-40..85	32	
		38-15-00	MAX 487 CPA	MAX	DIP8	-	●	-	0,25	0..70	128	
		38-17-32	MAX 487 CSA/SMD	MAX	-	S08	●	-	0,25	0..70	128	
		38-21-89	MAX 487 EESA/SMD	MAX	-	S08	●	-	0,25	-40..85	128	
		38-15-01	MAX 487 EPA	MAX	DIP8	-	●	-	0,25	-40..85	128	
		38-17-33	MAX 487 ESA/SMD	MAX	-	S08	●	-	0,25	-40..85	128	
		38-11-87	MAX 488 CPA	MAX	DIP8	-	-	●	0,25	0..70	32	
		38-21-34	MAX 488 CSA/SMD	MAX	-	S08	-	●	0,25	0..70	32	
		38-17-12	MAX 488 EPA	MAX	DIP8	-	-	●	0,25	-40..85	32	
		38-12-91	MAX 489 CPD	MAX	DIP14	-	-	●	0,25	0..70	32	
		38-12-95	MAX 489 CSD/SMD	MAX	-	S014	-	●	0,25	0..70	32	
		38-12-93	MAX 489 EPD	MAX	DIP14	-	-	●	0,25	-40..85	32	
		38-12-94	MAX 489 ESD/SMD	MAX	-	S014	-	●	0,25	-40..85	32	
		38-12-99	MAX 490 CPA	MAX	DIP8	-	-	●	2,5	0..70	32	
		38-13-02	MAX 490 CSA/SMD	MAX	-	S08	-	●	2,5	0..70	32	
		76-03-10	MAX 490 CSA+T/SMD ^a	MAX	-	S08	-	●	2,5	0..70	32	
		38-25-34	MAX 490 ECPA	MAX	DIP8	-	-	●	2,5	0..70	32	
		38-16-90	MAX 490 ECSA/SMD	MAX	-	S08	-	●	2,5	0..70	32	
		38-13-00	MAX 490 EPA	MAX	DIP8	-	-	●	2,5	-40..85	32	
		38-13-01	MAX 490 ESA/SMD	MAX	-	S08	-	●	2,5	-40..85	32	
		38-12-92	MAX 491 CPD	MAX	DIP14	-	-	●	2,5	0..70	32	
		38-12-98	MAX 491 CSD/SMD	MAX	-	S014	-	●	2,5	0..70	32	
		38-20-08	MAX 491 ECPD	MAX	DIP14	-	-	●	2,5	0..70	32	
		38-12-96	MAX 491 EPD	MAX	DIP14	-	-	●	2,5	-40..85	32	
		38-12-97	MAX 491 ESD/SMD	MAX	-	S014	-	●	2,5	-40..85	32	