

Part Number: 5025790000 Product Description: CLIK-Mate 1.50mm Pitch Crimp Terminal, Male, Tin Plating, 24-28 AWG,

Reel

Series Number: 502579 Status: Active

Product Category: Crimp Terminals Packaging Alternative: 5025790100 (Bag)

#### **Documents & Resources**

#### **Drawings**

Drawing 5025790000\_sd.pdf

### 3D Models and Design Files

3D Model 5025790000\_stp.zip

### Specifications

Application Specification AS-502578-001-001.pdf Application Specification AS-503149-001-001.pdf Application Specification AS-503395-001-001.pdf Packaging Specification SPK-502579-001-001.pdf Product Specification 5025780000-PS-000.pdf Product Specification 5025780001-PS-000.pdf Product Specification 5025780002-PS-000.pdf Product Specification 5025780003-PS-000.pdf Product Specification 5025781000-PS-000.pdf Product Specification 5025781000-PS-CHI-000.pdf Product Specification 5025781000-PS-JAP-000.pdf Product Specification 5025781002-PS-000.pdf Product Specification 5025781003-PS-000.pdf Product Specification 5031490000-PS-000.pdf Product Specification 5031491000-PS-000.pdf Product Specification 5031491001-PS-000.pdf Product Specification 5031491001-PS-JAP-000.pdf Product Specification 5031491003-PS-000.pdf

#### **Tooling Specifications**

Crimp Specification CS-502579-001-001.pdf

## **Product Environment Compliance**

### Compliance

GADSL/IMDS	Compliant with Exemption 44; 33
China RoHS	<b>©</b>

EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

### **Part Details**

#### General

Status	Active
Category	Crimp Terminals
Series	502579
Description	CLIK-Mate 1.50mm Pitch Crimp Terminal, Male, Tin Plating, 24-28 AWG, Reel
Application	Signal, Wire-to-Board
Product Family	CLIK-Mate Wire-to-Board Connectors
Product Name	CLIK-Mate
UPC	800756642857

### **Electrical**

Current - Maximum per Contact	2.0A
Voltage - Maximum	100V AC (RMS)/DC

## Physical

Durability (mating cycles max)	30
--------------------------------	----

Gender	Male
Material - Metal	Copper Alloy
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	42.000/mg
Packaging Type	Reel
Plating min - Mating	0.406µm
Plating min - Termination	0.406µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	0.78-1.28mm
Wire Size (AWG)	24, 26, 28
Wire Size mm²	0.08-0.20

## Use with Part(s)

Description	Part Number
1.50mm Pitch CLIK-Mate Single Row Plug Housings	502578
1.50mm Pitch CLIK-Mate Dual Row Plug Housings	503149

# **Application Tooling**

## Global

Description	Part Number
Hand Crimp Tool for 1.50mm Pitch CLIK-Mate Wire-to-Board Crimp Terminals, 24-28 AWG	2002187400
Extractor Tool for 1.50mm Pitch Wire-to-Board Crimp Terminal	638133700
FineAdjust Applicator for 1.50mm Pitch Wire-to-Board Crimp Terminals	639025000
T2 Terminator for 1.50mm Pitch Wire-to-Board Terminal	639125000

# **Application Tooling**

# Japan

Description	Part Number
-------------	-------------

S-1 Applicator for CLIK-Mate Plug
Terminals, 24-28 AWG

5780473700

This document was generated on May 02, 2024