

Műszaki adatok

Eaton UTS6JC14E19P



A fotó reprezentatív

Plastic plug, with cable gland backshell, with 19 male solder contacts, IP68/69K in unmated conditions; UTS6JC14E19P

General specifications

PRODUCT NAME	Eaton Souriau UTS series plastic waterproof IP68/69k connector
CATALOG NUMBER	UTS6JC14E19P
PRODUCT LENGTH/DEPTH	71.5 mm
PRODUCT HEIGHT	34.4 mm
PRODUCT WIDTH	34.6 mm
PRODUCT WEIGHT	44.6 g
COMPLIANCES	IEC 61984 (please contact us for more details) ROHS exemption 6.c UL 1977 (please contact us for more details) CSA-C22.2 No.182.3 (please contact us for more details)



Termékjellemzők

CURRENT RATING	5 A IEC
----------------	---------

Erőforrások

	4 A UL
ENVIRONMENTAL CONDITIONS	REACH RoHS Flammability rating UL94 HB
ENVIRONMENTAL RESISTANCE	Resistant against mineral oil Resistant against basic bath Vibrations level Per IEC 60512-4 - from 10 to 2000 Hz Resistant against gasoline Resistant against acid bath UV resistant, no degradation after 5 years of exposure in natural environment Resistant against oil
TEST CURRENT	4 A UL 4 A CSA 5 A IEC
TEST VOLTAGE	250 V UL 32 V IEC 250 V CSA
BACKSHELL ANGLE	Straight
BACKSHELL TYPE	Sealing Gland
CONNECTOR ACCESSORY OPTION	Delivered with connector
CONNECTOR ORIENTATION	N
CONNECTOR TYPE	Plug
CONTACT DELIVERY	Loaded
CONTACT GENDER	Pin (Male)
CONTACT PLATING	Gold
CONTACT TYPE	Solder Cup
COUPLING TYPE	1/3 Bayonet
DEGREE OF PROTECTION	IP68
INSERT MATERIAL	Neoprene
LAYOUT	19
PLUG TYPE	Straight Plug
SHELL MATERIAL	Plastic
SHELL SIZE	14
CABLE DIAMETER - MAX	14 mm
CABLE DIAMETER - MIN	5 mm
MATING CYCLES	250
OPERATING TEMPERATURE - MAX	105 °C
OPERATING TEMPERATURE - MIN	-40 °C
NUMBER OF CONTACTS	19
NUMBER OF CAVITY #20	19
SALT SPRAY	500 hour

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DÁTUM:



Eaton Corporation plc
Eaton House
30 Pembroke Road
DUBLIN, ÍRORSZÁG...
Eaton.com

© 2025 Eaton. Minden jog
fenntartva.

Az Eaton bejegyzett védjegy.

Minden más védjegy azok
tulajdonosainak tulajdonát képezi.

Follow us on social media to get the latest
product and support information.

