

Data sheet Product FK 250 10 LF PAK TR



Board Level heatsinks>Copper heatsinks for D PAK and others

- direct PCB mounting thru solderable surface
available standard packing: loose parts (**bulk goods**) or reel (**TR** = tape and reel)
- **tape width:** 24 mm, **reel diameter:** 330 mm, **quantity:** FK 250 06 = 450, FK 250 08 = 450, FK 250 10 = 350


Features

for transistor:


- SOT 223
- Power SO 8
- D³ PAK (TO 268)
- Power_SO_20
- SO-14
- D² PAK (TO 263)
- Power SO 10
- D PAK (TO 252)
- SOT 669 LF PAK
- SO-16
- SO IC 8 FL MP
- SO-8
- Power SO 36

width:	15 mm
height:	10 mm
length:	8 mm
thermal resistance:	28.8 K/W
surface:	solderable surface
material:	copper (Cu)
material thickness:	0.6 mm

Technical Drawing



28,8 K/W



Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28
58511 Lüdenscheid

Telefon +49 2351 435-0
Telefax +49 2351 45754

info@fischerelektronik.de
www.fischerelektronik.de