

	Cikkszám	Típus	Gyártó	Tokozás		WDT	Reset ki		Ures. [V]	twd [sec.]	Hőtart. [°C]
				Normál	SMD		H	L			
DIP20	38-12-37	MAX 810 REUR-T/SMD (AL)	MAX	-	SOT-23	-	●	-	2,63	-	-40..105
DIP28	38-12-38	MAX 810 SEUR-T/SMD (AK)	MAX	-	SOT-23	-	●	-	2,93	-	-40..105
	38-12-39	MAX 810 TEUR-T/SMD (AJ)	MAX	-	SOT-23	-	●	-	3,08	-	-40..105
	38-10-37	MAX 8211 EPA	MAX	DIP8	-	-	●	-	var.	-	-40..85
DIP8	38-25-56	MAX 8211 CSA/SMD	MAX	-	S08	-	●	-	var.	-	-40..85
	38-10-38	MAX 8212 EPA	MAX	DIP8	-	-	-	●	var.	-	-40..85
	38-29-85	MB 3773 PH-E1#	FUJ	DIP8	-	●	●	-	4,2	var.	-40..85
SOT-23	38-15-35	MB 3773 PS	FUJ	SIP8	-	●	●	●	4,2	var.	-40..85
	76-00-37	MC 33064 D-5G/SMD	ONS	-	S08	-	-	●	4,6	-	-40..85
	38-28-85	MC 33064 P-5G	ONS	TO-92	-	-	-	●	4,6	-	-40..85
SOT-89	38-27-70	MC 33164 P-5G	ONS	TO-92	-	-	-	●	4,33	-	-40..125
	38-28-76	MC 34064 P-5G	ONS	TO-92	-	-	-	●	4,6	-	0..70
	38-30-40	MC 34161PG	ONS	DIP8	-	-	-	●	2,54	-	-40..105
SSOP28	38-19-69	MCP 130-450DI/TO	MI	TO-92	-	-	-	●	4,25..4,5	-	-40..85
	38-24-35	MCP 130-450FI/TO	MI	TO-92	-	-	-	●	4,25..4,5	-	-40..85
	76-02-82	MCP 130T-450I/TT	MI	-	SOT-23	-	-	●	4,25..4,5	-	-40..85
TO-92	76-03-06	MCP 130T-460I/TT	MI	-	SOT-23	-	-	●	4,35..4,6	-	-40..85
	38-20-20	TC 1232 CPA-MI	MI	DIP8	-	●	●	●	4,5..4,75	0,15/0,6/1,2	0..70
	38-19-68	TL 7705 ACP/A-STM	STM	DIP8	-	-	●	●	4,55	-	0..70
SSOP28	38-04-83	TL 7705 ACP-TI	TI	DIP8	-	-	●	●	4,55	-	0..70
	43-00-20	TL 7705 ACD/SMD	TI	-	S08	-	●	●	4,55	-	0..70
	38-30-02	TL 7705 AIP	TI	DIP8	-	-	●	●	4,55	-	-40..85
TO-92	38-04-84	TL 7709 ACP-TI	TI	DIP8	-	-	●	●	7,6	-	0..70
	38-12-44	TLC 7705 IP-TI	TI	DIP8	-	-	●	●	4,55	-	-40..85
	38-23-47	TL 7757CPK	TI	-	SOT-89	-	-	●	4,55	-	0..70
SSOP28	76-02-81	TL 7757CPKG4/SMD	TI	-	SOT-89	-	-	●	4,55	-	0..70
	38-18-99	TPS 3305-18D/SMD	TI	-	S08	●	-	●	2,93/1,68	1,6	-40..85
	38-23-28	TPS 3809K33DBVT/SMD	TI	-	SOT-23	-	-	●	2,93	-	-40..85
TO-92	38-24-04	TPS 3836K33DBVT/SMD	TI	-	SOT-23/5	-	-	●	2,93	-	-40..85

A/D-ÁTALAKÍTÓK

	Cikkszám	Típus	Gyártó	Tokozás		Felbontás [bit]	Sebesség	Belső ref. [V]	Interfész	Hőtart. [°C]
				Normál	SMD					
K	38-06-03	AD 7569 JN	AD	DIP24	-	8	2 μs	1,25	párhuzamos	0..70
	38-19-72	AD 7575 JN	AD	DIP18	-		5 μs	-	párhuzamos	0..70
	38-08-82	AD 7828 LN	AD	DIP28	-		2,5 μs	-	párhuzamos	0..70
K	38-00-22	ADC 0803 LCN	NSC	DIP20	-		100 μs	-	párhuzamos	0..70
	38-00-23	ADC 0804 LCN	NSC	DIP20	-		100 μs	-	párhuzamos	0..70
	42-02-90	ADC 0808 CCN	NSC	DIP28	-		100 μs	-	párhuzamos	-40..85
K	38-06-05	ADC 0809 CCN	NSC	DIP28	-		100 μs	-	párhuzamos	-40..85
	38-15-69	ADC 0816 CCN	NSC	DIP40	-		100 μs	-	párhuzamos	-40..85
	38-21-55	ADC 0820 CCN	MAX	DIP20	-		1,4 μs	-	párhuzamos	0..70
K	38-30-72	ADC 0831 CCN	NSC	DIP8	-		32 μs	-	soros	0..70
	38-18-14	ADC 0832 CCN	NSC	DIP8	-		32 μs	-	soros	0..70
	38-07-43	ADC 0834 CCN	NSC	DIP14	-		32 μs	-	soros	0..70
K	38-16-47	ADC 0844 CCN	NSC	DIP20	-		60 μs	-	párhuzamos	0..70
	72-00-12	LTC 1098 CN8	LIN	DIP8	-		16 μs	-	soros	0..70
	38-18-46	MAX 1112 CPP	MAX	DIP20	-		25 μs	4,096	soros	0..70
K	38-20-11	MAX 114 CAG/SMD	MAX	-	SSOP24		0,66 μs	-	párhuzamos	0..70
	38-12-85	MAX 118 CPI	MAX	DIP28	-		0,66 μs	-	párhuzamos	0..70
	38-25-16	MAX 118CAI/SMD	MAX	-	SSOP28		0,66 μs	-	párhuzamos	0..70
K	38-12-87	MAX 153 CPP	MAX	DIP20	-		0,66 μs	-	párhuzamos	0..70
	38-13-91	TLC 542 CN	TI	DIP20	-		20 μs	-	soros	0..70
	38-24-48	TLC 542 IN	TI	DIP20	-		20 μs	-	soros	-40..85
K	38-12-80	TLC 549 CD/SMD	TI	-	S08		17 μs	-	soros	0..70
	38-08-40	TLC 549 CP	TI	DIP8	-		17 μs	-	soros	0..70
	38-24-40	TLC 549 ID/SMD	TI	-	S08		17 μs	-	soros	-40..85
K	38-24-39	TLC 549 IP	TI	DIP8	-		17 μs	-	soros	-40..85
	76-00-31	TLC 5510 INS/SMD	TI	-	S024W		20 Msps	-	párhuzamos	-40..85
	38-23-41	TLC 5540 INS/SMD-300	TI	-	S024NS		40 Msps	2	párhuzamos	-40..85